



MODEL DOG-275 24K



THE N&N ADVANTAGE

Tough and versatile, N&N Gooseneck Series flatbed trailers benefit from standard and optional features that allow you to safely haul excavating equipment, farm machinery and lifting platforms as well as palleted goods.

STANDARD FEATURES

- Galvanized axles
- Heat shrink connectors
- Toolbox between gooseneck H-beam
- Cold-weather harness
- Fifthweel or ball coupler
- Slipper spring suspension
- 12"@22 lb H-beam main frame

- 3" C-channels cross member on 12" C/C
- Stabilizer legs
- 2 x 12 000 lb drop leg jack
- Side pocket with rail
- Side D-rings on +/- 48" C/C
- 5 feet beavertail drop
- LED lights

- 37" ground clearance
- Radial tires on galvanized rims
- Loading light
- Back-up light
- Footstep on front

SPECIFICATIONS

USABLE WIDTH	97 ½ inches
USABLE LENGTH	391 ½ inches
AXLES	2 x 12,000 lb
BRAKES	Electric
TIRES	ST-235/85R16 – 12 ply dual wheel ST-245-70R17.5 – 16 ply single wheel
WEIGHT WHEN EMPTY	8,000 lb
LOAD CAPACITY	20,000 lb
TRAILER LENGTH	501 inches
TRAILER WIDTH	102 inches
DECKING	2" x 8" spruce planks
RAMPS	40" Spring assisted flip-over ramps
FINISH	Hot dipped galvanized







